



# How To Replace A Subaru Outback Exhaust Front Cover

Replacement of a cracked or damaged exhaust front cover on a Subaru Outback.

Written By: redacted



## INTRODUCTION

If you have a cracked or damaged exhaust front cover creating noises that can be heard when driving, this guide will help you replace it!



### TOOLS:

- [12mm Combination Wrench](#) (1)
- [Safety Glasses](#) (1)
- [Flashlight](#) (1)



### PARTS:

- [Exhaust Front Cover: 59020AG14C](#) (1)
-

## Step 1 — Exhaust Front Cover



- Collect Supplies.
- ⓘ Make sure the new Exhaust Front Cover is free of stickers, oil, or residues.

## Step 2



- Park Outback on a level dry and clean surface.
- ⚠ Make sure that the car is in park for an automatic transmission or in first gear for a manual transmission. Verify that the parking brake is engaged.




## Step 3



- ⚠ Put on safety glasses. Be sure to leave them on until the fix is complete.
- ⚠ Do not touch any exhaust components until you have verified that there is no danger of getting burned.
- Laying on your back, maneuver yourself underneath the driver or passenger side of the car carrying the 12mm combination wrench. Locate yourself about even with the back of the front door.

## Step 4



- Unplug the rear oxygen sensor connector and carefully route the wires through the Exhaust Front Cover so they are no longer passing through it.

## Step 5



- Locate the four mounting bolts for the Exhaust Front Cover.
- Remove the bolts by turning them counterclockwise using the 12mm combination wrench.

## Step 6



- Remove the old Exhaust Front Cover taking care to prevent damage to the vehicles undercoating and the oxygen sensor wires.

To reassemble your exhaust front cover, follow these instructions in reverse order.

This document was last generated on 2017-06-16 02:50:52 PM.